

ASPHALT PAVER

SPECIFICATIONS

DIMENSIONS, MEASURES & WEIGHTS

Overall Height	7'1"
Transport Width	8'6"
Operating Width	10'5"
Length	9'7"
Truck clearance	23"
Operating Weight	10,600 lbs.

ENGINE

Type	Diesel
Net Power	48hp @ 3000 rpm
Fuel Tank	12.5 gal.

SCREED

Full Floating & Adjustable	8' – 13,
Vibratory	3000 vpm – maximum
Propane-Heated	Standard
Hydraulic Extensions	30"w/6" wear plate
Crown/Invert Adjustment	Single Lever , 0"-3"

MATERIAL FLOW

Independent Hydraulic Operated Gates	Standard
Gate Cut-Off Plates	Option 6"-36"
Gravity Flow Asphalt Hopper Capacity	6 tons
Independent Hydraulic Operating Augers	Located on the Gate or Screed Extension

DRIVE CONFIGURATION

Speed	Single, 0-1`30 FPM
Self-Adjusting, Steel Track	12" x 3"
Counter-Rotating	Standard
Fine Tune Steering Valve	Standard
Track Length	48"

OPERATOR STATION

Platform	Isolated Dual-Span
Controls	Left & Right Sides
Wash-Down Stations	Dual, 5.5 gal.

HYDRAULIC SYSTEM

Vairable Hydrostatic Drive Pump	37.0 gpm
Hydraulic Auger Drive Pump	10.9 gpm
Hydraulic Cylinder Pump	10.9 gpm
Hydraulic Oil Cooler Capacity	32 gpm
Hydraulic Reservoir	20 gal.

PERFORMANCE

Paving Width	
Minimum	4'
Standard	8'
Maximum	13'
Paving Depth	0"-6"
Hydraulic Feed Auger	2
Hydraulic Material Flow Gates	2