

BID SPECIFICATIONS MID-MOUNT ZERO TURN MOWER

SPECIFICATIONS

Engine	27 -29 Horse Power Kawasaki or equivalent Cooling – Air Cooled Air Cleaner – Heavy duty canister Engine Warranty – 3 year
Drive System-	Dual hydrostatic Pumps – 21cc Hydro-Gear PY pumps Hydraulic Cooling – Oil cooler with 8” fan
Ground Speed-	0 to 14 mph
Cutting Deck-	60” side discharge , Cutting Heights 1” to5.5” , Deck Lift Foot Operated , Spindles – Ductile Cast iron with steel shafts and Sealed ball bearings , Drive – Electric PTO clutch , Construction- 11ga.+ 11 ga. + 7ga.welded steel
Cutting Height-	Adjustable from operator lift. Quick-Lift deck assist.
Deck Lift-	Manual lift with Quick-Lift deck assist, which uses leg power To aid in raising deck. Operator can raise deck into transport Position from operator’s seat, without changing cutting height
Seat	Bolstered Grammer suspension seat
Drive Tires-	24 x 12x 12
Front Caster Tires-	13 x 6.50-6
Casters-	front casters wheels mounted with sealed ball bearings Front Caster Forks – Fabricated ½”steel
Curb Weight-	1511 lbs.
Dimensions-	
Width	
60” Side Discharge	Deflector Up 66” Deflector Down ”